

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 10/18/2023

Version: 1.3

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

<u>Product Identifier</u> <u>Product Form:</u> Mixture

Product Name: Freezer Cleaner Product Code: AFCO 5663 Intended Use of the Product

Use of the Substance/Mixture: Freezer/low temperature cleaner. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company AFCO

800 Development Avenue Chambersburg, PA 17201

T: 800-345-1329 www.afcocare.com

**Emergency Telephone Number** 

Emergency Number : 1-800-424-9300 (CHEMTREC)

# **SECTION 2: HAZARDS IDENTIFICATION**

## **Classification of the Substance or Mixture**

#### Classification (GHS-US)

Flam. Liq. 3 H226 Skin Irrit. 3 H316 Eye Irrit. 2A H319 Aquatic Acute 2 H401

# Label Elements GHS-US Labeling

Hazard Pictograms (GHS-US)





Signal Word (GHS-US) : Warning.

Hazard Statements (GHS-US) : H226 - Flammable liquid and vapor

H316 - Causes mild skin irritation H319 - Causes serious eye irritation

H401 - Toxic to aquatic life

Precautionary Statements (GHS-US): P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, and lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, eye protection, face protection. P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use appropriate media for extinction.

10/18/2023 EN (English US) 1/10

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to local, regional, national, territorial, provincial, and international regulations.

#### **Other Hazards**

**Other Hazards Not Contributing to the Classification**: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes.

**Unknown Acute Toxicity (GHS-US)** Not available.

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

## **Substances**

#### **Mixture**

Name	Product identifier	% (w/w)	Classification (GHS-US)
Water	(CAS No) 7732-18-5	30-40	Not classified
Ethyl alcohol	(CAS No) 64-17-5	40-50	Flam. Liq. 2, H225
			Eye Irrit. 2A, H319
			Aquatic Acute 2, H401
1-Methoxy-2-propanol	(CAS No.) 107-98-2	20-30	Flam. Liq. 3, H226
			Repr. 1B, H360
			STOT SE 3, H336
2-Butoxyethanol	(CAS No) 111-76-2	1-5	Flam. Liq. 4, H227
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
			Acute Tox. 4 (Inhalation: vapour), H332
			Skin Irrit. 2, H315
			Eye Irrit. 2A, H319
D-Glucopyranose, oligomeric, decyl octyl glycosides	(CAS No) 68515-73-1	0.1-1	Eye Dam. 1, H318
Ethanolamine	(CAS No) 141-43-5	0.1-1	Flam. Liq. 4, H227
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
			Acute Tox. 4 (Inhalation: vapour), H332
			Skin Corr. 1B, H314
			Eye Dam. 1, H318
			STOT SE 3, H335
			Aquatic Acute 2, H401
			Aquatic Chronic 3, H412

Full text of H-phrases: see section 16.

# **SECTION 4: FIRST AID MEASURES**

# **Description of First Aid Measures**

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or doctor/physician.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

#### Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes mild skin irritation and serious eye irritation. Effects of exposure (ingestion or skin or eye contact) to substance may be delayed.

Inhalation: May cause slight irritation to respiratory tract.

10/18/2023 EN (English US) 2/10

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Skin Contact:** Contact may cause mild irritation. **Eye Contact:** Causes serious eye irritation.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Not available.

## Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

## **SECTION 5: FIREFIGHTING MEASURES**

#### **Extinguishing Media**

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam, dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

#### Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture.

Reactivity: Thermal decomposition generates: Carbon dioxide and carbon monoxide.

#### **Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire. **Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>).

Other information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections: Refer to section 9 for flammability properties.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid breathing vapours, mist, and spray. Avoid all contact with skin, eyes, or clothing. Keep away from heat, sparks, open flames, hot surfaces. - No smoking.

## For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

**For Emergency Personnel** 

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

#### **Environmental Precautions**

Prevent entry to sewers and public waters. Avoid release to the environment.

#### Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

Reference to Other Sections: See heading 8, Exposure Controls and Personal Protection.

# **SECTION 7: HANDLING AND STORAGE**

#### **Precautions for Safe Handling**

Additional Hazards When Processed: Keep away from heat, sparks, open flames, hot surfaces. - No smoking.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do no eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling. Wash contaminated clothing before reuse.

#### **Conditions for Safe Storage, Including Any Incompatibilities**

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from extremely high temperatures, heat, sparks, ignition sources, open flames and incompatible materials.

Incompatible Materials: Strong oxidizers.

10/18/2023 EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Specific End Use(s)**: Freezer/low temperature cleaner. For professional use only.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

# **Control Parameters**

Ethanolamine (141-43-5)		
Mexico	OEL TWA (mg/m³)	8 mg/m³
Mexico	OEL TWA (fig/fit )	3 ppm
Mexico	OEL STEL (mg/m³)	15 mg/m³
Mexico	OEL STEL (ppm)	6 ppm
USA ACGIH	ACGIH TWA (ppm)	3 ppm
USA ACGIH	ACGIH STEL (ppm)	6 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	6 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (Ing/III )	3 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	8 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (IIIg/III )	3 ppm
USA NIOSH	NIOSH REL (TWA) (ppiii) NIOSH REL (STEL) (mg/m³)	15 mg/m <sup>3</sup>
USA NIOSH	, , , , , ,	
	NIOSH REL (STEL) (ppm)	6 ppm
USA IDLH	US IDLH (ppm)	30 ppm
Ontario Ontario	OEL TWA (npm)	6 ppm
	OEL TWA (ppm)	3 ppm
Québec	VECD (mg/m³)	15 mg/m³
Québec	VECD (ppm)	6 ppm
Québec	VEMP (mg/m³)	7.5 mg/m <sup>3</sup>
Québec	VEMP (ppm)	3 ppm
Ethyl alcohol (64-17-5)		
Mexico	OEL TWA (mg/m³)	1900 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	1000 ppm
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1900 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
Ontario	OEL STEL (ppm)	1000 ppm
Québec	VEMP (mg/m³)	1880 mg/m³
Québec	VEMP (ppm)	1000 ppm
2-Butoxyethanol (111-76-2)		
Mexico	OEL TWA (mg/m³)	120 mg/m³
Mexico	OEL TWA (ppm)	26 ppm
Mexico	OEL STEL (mg/m³)	360 mg/m <sup>3</sup>
Mexico	OEL STEL (ppm)	75 ppm
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	24 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	700 ppm
Ontario	OEL TWA (ppm)	20 ppm
Québec	VEMP (mg/m³)	97 mg/m³
Québec	VEMP (ppm)	20 ppm
	,, ,	1

10/18/2023 EN (English US) 4/10

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1-Methoxy-2-propanol (107-98-2)		
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA ACGIH	ACGIH STEL (ppm)	100 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	360 mg/m³
USA NIOSH	NIOSH REL (ST) (ppm)	150 ppm

#### **Exposure Controls**

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment. If user operations generate fumes, vapors, gas, or spray use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or regulatory limits.

Personal Protective Equipment: Protective goggles. Face shield. Gloves.







Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

**Skin and Body Protection:** Wear suitable protective clothing.

Respiratory Protection: A respirator is not needed under normal and intended conditions of product use. Whenever worker

exposure may exceed established regulatory exposure limits, use a NIOSH-approved respirator.

Other Information: When using, do not eat, drink or smoke.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## **Information on Basic Physical and Chemical Properties**

Physical State: LiquidAppearance: Clear, amberOdor: AlcoholOdor Threshold: Not available

**pH** : 11.0

Relative Evaporation Rate (butylacetate=1): Not availableMelting Point: -30°F (-34°C)Freezing Point: Not availableBoiling Point: 180°F (82°C)Flash Point: 25°C (77°F)Auto-ignition Temperature: None

Decomposition Temperature: Not availableFlammability (solid, gas): Not availableLower Flammable Limit: Not availableUpper Flammable Limit: Not availableVapor Pressure: Not availableRelative Vapor Density at 20°C: Not available

Specific Gravity: 0.92Solubility: CompleteLog Pow: Not availableLog Kow: Not availableViscosity, Kinematic: Not availableViscosity, Dynamic: Not availableExplosion Data – Sensitivity to Mechanical Impact: Not available

10/18/2023 EN (English US) 5/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Explosion Data – Sensitivity to Static Discharge** : Not available

## **SECTION 10: STABILITY AND REACTIVITY**

**Reactivity:** When heated to decomposition, emits toxic fumes. **Chemical Stability:** Stable at standard temperature and pressure.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Extremely high temperatures, heat, sparks, open flames, ignition sources. Incompatible materials.

**Incompatible Materials:** Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO<sub>2</sub>).

## **SECTION 11: TOXICOLOGICAL INFORMATION**

# <u>Information on Toxicological Effects - Product</u>

Acute Toxicity: Not classified LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes mild skin irritation. pH: 11.0 Serious Eye Damage/Irritation: Causes serious eye damage. pH: 11.0

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

**Teratogenicity:** Not available **Carcinogenicity:** Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause slight irritation to respiratory tract

Symptoms/Injuries After Skin Contact: Contact may cause mild irritation

**Symptoms/Injuries After Eye Contact:** Causes serious eye damage

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

LD30 alia LC30 Data.	
Water (7732-18-5)	
LD50 Oral Rat	>90,000 mg/kg
Ethanolamine (141-43-5)	
LD50 Oral Rat	1,720 mg/kg
LD50 Dermal Rabbit	1 ml/kg
1-Methoxy-2-propanol (107-98-2)	
LD50 Oral Rat	4,016 mg/kg
LD50 Dermal Rabbit	>2,000mg/kg
Ethyl alcohol (64-17-5)	
LD50 Oral Rat	10,470 mg/kg
LD50 Dermal Rat	20 ml/kg
LC50 Inhalation Rat (mg/l)	124.7 mg/l/4h
2-Butoxyethanol (111-76-2)	
LD50 Oral Rat	470 mg/kg
LD50 Dermal Rat	1,680 mg/kg
LC50 Inhalation Rat (ppm)	450 ppm/4h
ATE (dermal)	0.680 mg/kg body weight
ATE (gases)	450.000 ppmV/4h
ATE (vapors)	11.000 mg/l/4h
IARC Group	3

10/18/2023 EN (English US) 6/10

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.

# **SECTION 12: ECOLOGICAL INFORMATION**

Toxicity Ecology - General: Harmful to aquatic life.

Toxicity ecology - General: Harriful to aquatic life.		
1-Methoxy-2-propanol (107-98-2)		
	6812 mg/l (Exposure time: 96 h – Species: Leuciscus idus [static])	
	21100-25900 mg/l (Exposure time: 48 h – Species: Daphnia magna)	
	≥1000 mg/l (Exposure time: 96 h – Species:Oncorhynchus mykiss [semi-static])	
13-5)		
	227 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
	65 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Organisms 1	15 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)	
	3684 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])	
Ethyl alcohol (64-17-5)		
9.468 (9.468 - 12.6	i24) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) converted from ml/l	
	9268 (9268 - 14221) mg/l (Exposure time: 48 h - Species: Daphnia magna)	
	100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
2-Butoxyethanol (111-76-2)		
	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	
	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)	
	ol (107-98-2) 3-5) Organisms 1 5) 9.468 (9.468 - 12.6	

## **Persistence and Degradability**

Freezer Cleaner (AFCO 5663)	
Persistence and Degradability	Not established.

# **Bioaccumulative Potential**

<u> Dioaccamaiative i otentiai</u>	
Freezer Cleaner (AFCO 5663)	
Bioaccumulative Potential	Not established.
Ethanolamine (141-43-5)	
Log Pow	-1.91 (at 25°C/77°F)
Ethyl alcohol (64-17-5)	
Log Pow	-0.32
Bioaccumulative Potential	Not established.
2-Butoxyethanol (111-76-2)	
Log Pow	0.81 (at 25°C/77°F)

**Mobility in Soil** Not available.

# **Other Adverse Effects**

Other Information: Avoid release to the environment.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

# **SECTION 14: TRANSPORT INFORMATION**

# 14.1 In Accordance with DOT

**Proper Shipping Name** : ETHANOL SOLUTIONS

Hazard Class : 3
Identification Number : UN1170
Label Codes : 3
Packing Group : II
ERG Number : 127
14.2 In Accordance with IMDG



10/18/2023 EN (English US) 7/10

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name : ETHANOL SOLUTIONS

Hazard Class : 3

Identification Number : UN1170

Packing Group : II
Label Codes : 3
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D



#### 14.3 In Accordance with IATA

Proper Shipping Name : ETHANOL SOLUTIONS

Packing Group : II

**Identification Number** : UN1170

Hazard Class: 3Label Codes: 3ERG Code (IATA): 3L



## 14.4 In Accordance with TDG

Proper Shipping Name : ETHANOL SOLUTIONS

Packing Group : II
Hazard Class : 3
Identification Number : UN1170

Label Codes : 3



## **SECTION 15: REGULATORY INFORMATION**

#### **US Federal Regulations**

Freezer Cleaner (AFCO 5663)		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard.	
	Delayed (chronic) health hazard.	
	Flammable hazard.	

#### Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

#### D-Glucopyranose, oligomeric, decyl octyl glycosides (68515-73-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

# 1-Methoxy-2-propanol (107-98-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

#### Ethanolamine (141-43-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

#### Ethyl alcohol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

## 2-Butoxyethanol (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

#### **US State Regulations**

#### Ethyl alcohol (64-17-5)

- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas City of Austin Aerosol Paint and Glue Restrictions
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

#### 2-Butoxyethanol (111-76-2)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. New Jersey Right to Know Hazardous Substance List

10/18/2023 EN (English US) 8/10

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits Skin Designations
- U.S. New York Occupational Exposure Limits TWAs
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

#### **Ethanolamine (141-43-5)**

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

#### D-Glucopyranose, oligomeric, decyl octyl glycosides (68515-73-1)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

#### 1-Methoxy-2-propanol (107-98-2)

- U.S. Massachusetts RTK (Right to Know) List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

## **Canadian Regulations**

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### Ethanolamine (141-43-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### Ethyl alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

# 2-Butoxyethanol (111-76-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### D-Glucopyranose, oligomeric, decyl octyl glycosides (68515-73-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### 1-Methoxy-2-propanol (107-98-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.

# **SECTION 16: OTHER INFORMATION**

**Revision date** : 10/18/2023

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

#### **GHS Full Text Phrases:**

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Acute Tox. 4 (Inhalation: vapour)	Acute toxicity (inhalation: vapour) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A

10/18/2023 EN (English US) 9/10

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Repr. 1B	Reproductive toxicity Category 1B
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Irrit. 3	Skin corrosion/irritation Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H316	Causes mild skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H360	May damage fertility or the unborn child
H401	Toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA Fire Hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

**HMIS III Rating** 

**Health** : 2 Moderate Hazard - Temporary or minor injury may occur.

Flammability : 3 - Serious Hazard.
Physical : 0 - Minimal Hazard.

# Party Responsible for the Preparation of This Document

**AFCO** 

800 Development Avenue Chambersburg, PA 17201

T: 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS SDS 2015 (U.S., Can., Mex.)

10/18/2023 EN (English US) 10/10